

RevNo	Revision note	Date
▲		
▲		
▲		

NOTE:

1. Actual Attenuation Supplied on Test Result Sheet per Individually Packed Assembly
2. CABLE INFO :
 - Fiber Type could be Singlemode and Multimode Simplex
 - Core/Cladding/Buffering Diameter : 62.5/125, 50/125, 9/125.µm
 - Flame Resistance : UL-1666 (for riser and general building applications)
3. SC-FC Connector INFO :
 - Ferrule Type: Ceramic

40105-LL-Xn

LL : Fiber Length


Xn : Fiber Type (Example : 06 means OM1 62.5/125 µm; 05 means OM2 50/125 µm;

05a means OM3 50/125 µm aqua color; 09 means OS1 9/125 µm)

⑭	DUST CAP	1	PC.
⑬	FC CONNECTOR ASSEMBLY	1	PC.
⑫	CRIMP EYELET	1	PC.
⑪	STRAIN RELIEF BOOT	1	PC.
⑩	DUST CAP	1	PC.
⑨	HOUSING	1	PC.
⑧	PLUG FRAME	1	PC.
⑦	FERRULE	1	PC.
⑥	SPRING	1	PC.
⑤	STOP RING	1	PC.
④	RING	1	PC.
③	CRIMP EYELET	1	PC.
②	STRAIN RELIEF BOOT	1	PC.
①	FIBER OPTIC CABLE	1	PC.

ITEM	DESCRIPTION	Q'TY	UNIT
------	-------------	------	------

Designed by - date	Checked by - date	Approved by - date	Date	Size	Scale
			29/09/2009	A4	-

 HOSIWELL TECHNOLOGY CO., LTD.	Part Name	Fiber Patch Cord SC-FC Simplex	Unit	M.
	Part No.	40105-LL-Xn	Issued	1
	Ref. No.		Sheet	
	Used On.		1 of 1	