


Self Support Crane Control Cable


PVC insulated, PVC jacket 600 V

- Conductor: Fine stranded copper conductor
- Insulation: Color coded PVC insulation, Core cabled under fabric tape
- Jacket: PVC jacket with self supporting steel wire
- Rated: Temp. 75 °C. Voltage 600 V. Pass UL VW-1 and CSA FT1 vertical flame test
- Application: For vertical switch control of crane or electrical equipment.



Single Slings

Part Number	Number Of Conductor	Conductor		Insulation		Jacket Material	Jacket Nom. OD. (mm.)	Self Support Wire (mm.)	Jacket Color
		mm ²	No./mm.	Nom.Thickness (mm.)	Nom. OD. (mm.)				
HECR 125	5	1.25	52/0.18	0.76	3.0	PVC	11.7 x 19.2	3.0	Black
	8	1.25	52/0.18	0.76	3.0	PVC	15.5 x 23.0	3.0	Black
	10	1.25	52/0.18	0.76	3.0	PVC	16.0 x 23.5	3.0	Black
	14	1.25	52/0.18	0.76	3.0	PVC	17.3 x 24.8	3.0	Black
	20	1.25	52/0.18	0.76	3.0	PVC	21.0 x 28.5	3.0	Black



Double Slings

HECR 150	5	1.50	64/0.18	0.80	3.4	PVC	11.7 x 25.1	3.0	Black
	8	1.50	64/0.18	0.80	3.4	PVC	15.5 x 28.5	3.0	Black
	10	1.50	64/0.18	0.80	3.4	PVC	16.0 x 29.3	3.0	Black
	12	1.50	64/0.18	0.80	3.4	PVC	17.3 x 29.3	3.0	Black