


Self Support Crane Control Cable


PVC insulated, PVC jacket 600 V

- Conductor: Fine stranded copper conductor
- Insulation: Color coded PVC insulation, Core cabled under fabric tape
- Jacket: PVC jacket with self supporting steel wire
- Rated: Temp. 75 °C. Voltage 600 V. Pass UL VW-1 and CSA FT1 vertical flame test
- Application: For vertical switch control of crane or electrical equipment.



Single Slings

Part Number	Number Of Conductor	Conductor mm ²	No./mm.	Insulation Nom.Thickness (mm.)	Nom. OD. (mm.)	Jacket Material	Nom. OD. (mm.)	Self Support Wire (mm.)	Jacket Color
HECR 125	5	1.25	52/0.18	0.76	3.0	PVC	11.7 x 19.2	3.0	Black
	8	1.25	52/0.18	0.76	3.0	PVC	15.5 x 23.0	3.0	Black
	10	1.25	52/0.18	0.76	3.0	PVC	16.0 x 23.5	3.0	Black
	14	1.25	52/0.18	0.76	3.0	PVC	17.3 x 24.8	3.0	Black
	20	1.25	52/0.18	0.76	3.0	PVC	21.0 x 28.5	3.0	Black



Double Slings

HECR 150	5	1.50	64/0.18	0.80	3.4	PVC	11.7 x 25.1	3.0	Black
	8	1.50	64/0.18	0.80	3.4	PVC	15.5 x 28.5	3.0	Black
	10	1.50	64/0.18	0.80	3.4	PVC	16.0 x 29.3	3.0	Black
	12	1.50	64/0.18	0.80	3.4	PVC	17.3 x 29.3	3.0	Black