


RevNo	Revision note	Date
①		
②		
③		

- MATERIAL HOUSING—POLYCARBONATE, CLEAR.**
TERMINAL— PHOSPHOR BRONZE, PLATED WITH 0.381 μ m (.000015) MINIMUM THICK GOLD IN LOCALIZED GOLD PLATE AREA, GOLD FLASH OVER THE REMAINDER, OVER 2.54 μ m (.000100) MINIMUM THICK NICKEL UNDERPLATE.
SHIELD— COPPER ALLOY PLATED WITH 2.03 μ m (.000080) MINIMUM THICK TIN LEAD OVER 2.03 μ m (.000080) MINIMUM THICK COPPER UNDERPLATE.
- PLUG WILL ACCEPT 24 TO 28AWG. STRANDED WIRE**

①	RJ45 8P8C Cat.5e Plug for FTP/SFTP Strand Cable				1	PC.
ITEM	DESCRIPTION				Q'TY	UNIT
Designed by	date	Checked by -	date	Approved by -	date	Scale
					24/09/2009	A4
 HOSIWELL TECHNOLOGY CO., LTD.				Part Name		Unit
				RJ45 8P8C Cat.5e Plug		mm.
				Part No.		Issued
				21413		1
Ref. No.				Sheet		
Used On.				1 of 1		